



- **BUILD VOLUME 200 x 200 x 200**
- **SIMPLE OPERATION**
- **METAL BODY CONSTRUCTION**
- **EASY PRINTOUT REMOVAL**
- **BUILT-IN CAMERA**
- **PRINTOUTS FROM FLEXIBLE MATERIALS**
- **24-MONTH WARRANTY**
- **THE EXTRUDER MADE OF ALUMINIUM**

TECHNICAL SPECIFICATION

Print technology	FFF (fused filament fabrication)	Max. platform temp.	120°C
Build volume XYZ	200 x 200 x 200 mm	Nozzle	brass
Chamber	open (optional top cover)	Automatic Leveling	yes
Min. layer height	50 µm	Operating System	Windows 7 and later, MAC OS10.6.8 or later
Material	full metal body	Printer weight	23 kg
Max. head temperature	260 °C	Package Dimension	550 x 550 x 660 mm
Connections	Wi-Fi/USB Memory	Printer Dimension	411 x 395 x 475 mm
Slicing Software	OmniSuperSlicer/ Simplify3D/ inne	Power Support	100-240V/320W
Touch Screen	3,5" Full Color	Compatible files	.3mf, .obj, .stl, .gcode
Precision	+/-100 microns	XY Positioning Accuracy	10 microns
System Language	multi language	Resume printing after losing power	no
Filament diameter	1,75 mm	Warranty	24 months

FILAMENTS COMPATIBLE WITH OMNI200

ABS-42

It is a standard filament of high versatility, characterized by durability and mechanical strength. It is also a material that is known to be ease to processing.

ASA-39

This material is used in projects where there is a need for resistance to atmospheric conditions, especially UV resistance. It is also filament with high-quality wall finish and high strength.

HIPS-20

A filament used mainly to create supports during printing with all materials (except nylon). This material is also used in the metal industry to print lost molds due to its ease of firing.

TPU-93A

Flexible material with a hardness of 93A Shore. It has such features as low processing shrinkage, high durability and good bonding of tool components, e.g. those in contact with the car body, flexible hoses, holders and housing.

PLA-36

Biodegradable polymer, made from renewable resources. Universal, used in many industries. It is characterized by high precision and aesthetics of mase models, ease of printing and excellent adhesion between layers.

PET-G-32

Material with low shrinkage. It can be used to create highly accurate models. It is suitable for the food industry and medical applications as it can be sterilised.



COOPERATION WITH OMNI3D

1



PRE-IMPLEMENTATION AUDIT

Return on investment, cost-benefit analysis - these are just some of the elements of the audit prepared by 3D printing professionals.

2



SAMPLE PRINT

Check the print quality. Make a sample print of your model.

3



RANGE OF POSSIBILITIES

Equipment purchase, 3D printing on demand or printer rental. Choose the best option for your business.

4



TRAINING & SUPPORT

Client installation, employee training, technology support, and service.

sales@omni3d.com

www.omni3d.com

61 666 12 34



Rzeczpospolita
Polska



Unia Europejska
Europejski Fundusz
Rozwoju Regionalnego



intED LLP

62 Ubi Road 1, #06-10, Oxley Bizhub 2
Singapore 408734

Tel: 9232 1019

Fax: 6225 6167

email: benghuat@inted.sg

Website: www.inted.sg